BEM	SCM	CORPORATION
	SCIVI	CORPORATION

EN COATINGS & RESINS DIVISION CLID AVENUE CL. LLAND, OHIO 44115 EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

3187

SECTION I

- Low Luster Chamal - Latex

CODE IDENTIFICATION 3187

1317+30-2

DATE PRINTED PRODUCT IDENTIFICATION SPRED LO LUSTRE INTERMEDIATE T

02/14/86

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT

WEIGHT

PERCENT THRESHOLD LIMIT VALUE LEL PRESS.

VAPOR

TITANIUM DIOXIDE

CAS NO. -

10 MG/M3

ALUMINUM SILICATE_(CLAY)

CAS NO. -1335-30-4 5

10 MG/M3

THE THRESHOLD LIMIT VALUE (TLV) IS THE TIME WEIGHTED AVERAGE (TWA) TO WHICH IT IS BELIEVED THAT MOST WORKERS MAY BE EXPOSED 8-10 HOURS PER DAY; 40 HOURS PER WEEK WITHOUT ADVERSE HEALTH EFFECTS.

LEL - THE LOWER EXPLOSIVE LIMIT IS THE LOWEST CONCENTRATION (% OF VOLATILES IN AIR) THAT WILL PRODUCE A FLASH OF FIRE WHEN AN IGNITION SOURCE IS PRESENT.

SECTION III - PHYSICAL DATA

BOILING RANGE

NOT DETERMINED

WEIGHT PER GALLON

% VOLATILE BY VOLUME

73.77

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (SETA)

- ABOVE 200 F

LOWER EXPLOSIVE LIMIT NOT DETERMINED

COST (PSN)

PAINT

HAZARD CLASS

NOT RESTRICTED

EXTINGUISHING MEDIA

DRY CHEMICAL OR FOAM

SCM CORPORATION
EN COATINGS & RESINS DIVISION

S JCLID AVENUE CLL VELAND, OHIO 44115 EMERGENCY TELEPHONE NO. (216) 826-5566 The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

3187

PAGE

2

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

INUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR

FIRE.

SPECIAL FIRE FIGHTING PROCEDURES

WATER MAY BE USED TO COOL AND PROTECT EXPOSED CONTAINERS.

SECTION V - HEALTH HAZARD DATA

ROUTE OF ENTRY _ __ INHALATION

SKIN

EYES

INGESTION

TS OF OVEREXPOSURE

IRRITATION OF EYES, SKIN, RESPIRATORY TRACT.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION . MOVE PERSON TO WELL VENTILATED AREA.

GET EMERGENCY MEDICAL ATTENTION.

ADMINISTER DXYGEN OR ARTIFICIAL RESPIRATION IF NECESSARY.

SKIN CONTACT FLUSH FROM SKIN WITH WATER, THEN WASH THOROUGHLY WITH SOAP

AND WATER.

EYE CONTACT FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST

15 MINUTES. GET EMERGENCY MEDICAL ATTENTION.

INGESTION - GET EMERGENCY MEDICAL ATTENTION.

SECTION VI - REACTIVITY DATA

TABILITY STABLE

NCOMPATIBILITY *** NOT DETERMINED ***

SEM	SCM	CORPORATION
EN COATIN	IGS & RESIN	IS DIVISION

JCLID AVENUE CLEVELAND, OHIO 44115 EMERGENCY TELEPHONE NO. (216) 826-5566 The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

SECTION VI - REACTIVITY DATA

CONDITIONS TO AVOID

*** NOT DETERMINED ***

HAZARDOUS DECOMPOSITION PRODUCTS

CARBON MONOXIDE CARBON DIOXIDE

HAZARDOUS POLYMERIZATION

WILL NOT OCCUR

SECTION VII - SPILL OR LEAK PROCEDURES

AS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA.

MASTE DISPOSAL DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS.

SECTION VIII - SPECIAL PROTECTION INFORMATION

ESPIRATORY PROTECTION

CONTROL ENVIRONMENTAL CONCENTRATIONS BELOW APPLICABLE STANDARDS. WHERE RESPIRATORY PROTECTION IS REQUIRED, USE ONLY NIOSH/MSHA APPROVED RESPIRATORS IN ACCORDANCE WITH OSHA STANDARD 29 CFR 1910-134.

'ENTILATION

PROVIDE DILUTION VENTILATION OR LOCAL EXHAUST TO PREVENT BUILD-UP OF VAPORS.

'ERSONAL PROTECTIVE EQUIPMENT

EYE WASH SAFETY SHOWER SAFETY GLASSES OR GOGGLES



YEN COATINGS & RESINS DIVISION
9(CLID AVENUE
CLL VELAND, OHIO 44115
EMERGENCY TELEPHONE NO. (216) 826-5566

The information contained herein is based on data available at the time of preparation of this data sheet and which SCM Corporation believes to be reliable. However, no warranty is expressed or implied regarding the accuracy of this data. The SCM Corporation shall not be responsible for the use of this information, or of any product, method or apparatus mentioned and you must make your own determination of its suitability and completeness for your own use, for the protection of the environment, and the health and safety of your employees and users of this material.

3187

PAGE

SECTION IX - SPECIAL PRECAUTIONS

HANDLING AND STORAGE

STORE BELOW 100 F. KEEP FROM FREEZING.

JTHER PRECAUTIONS

USE ONLY WITH ADEQUATE VENTILATION.

DO NOT TAKE INTERNALLY.

KEEP BUT OF REACH OF CHILDREN.

AVOID CONTACT WITH SKIN AND EYES, AND BREATHING OF VAPORS.

WASH HANDS THOROUGHLY AFTER HANDLING, ESPECIALLY BEFORE

EATING OR SMOKING.

KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.

AVOID BREATHING SANDING DUST.